

# The Domain Name System

---

# History of DNS

## ❑ Before DNS

- ARPAnet
  - *HOSTS.txt* contains all the hosts' information
  - Maintained by SRI's Network Information Center
    - In SRI-NIC host
- Problems: Not scalable!
  - Traffic and Load
  - Name Collision
  - Consistency

## ❑ Domain Name System

- Administration decentralization
- 1984
  - Paul Mockapetris (University of Southern California)
  - RFC 882, 883 → 1034, 1035
    - 1034: Concepts
    - 1035: Implementation and Specification

RFC Sourcebook:

<http://www.networksorcery.com/enp/default0304.htm>

# DNS Introduction

## – DNS Specification

---

□ Make domain name system as

- Tree architecture
  - Each subtree → “*domain*”
  - Domain can be divided in to “*subdomain*”
- Distributed database
  - Each site maintains segment of DB
  - Each site open self information via network
- Client-Server architecture
  - Name servers provide information (Name Server)
  - Clients make queries to server (Resolver)

# DNS Introduction

## – Domain and Subdomain


### □ DNS Namespace

- A tree of domains


### □ Domain and subdomain

- Each domain has a “domain name” to identify its position in database
  - EX: nctu.edu.tw
  - EX: cs.nctu.edu.tw

*DNS  
database*



*DNS database*



# The DNS Namespace (1)

## □ A inverted tree (Rooted tree)


- Root with label “.”

## □ Domain level

- Top-level or First level
  - Child of the root
- Second-level
  - Child of a First-level domain

## □ Domain name limitation

- 63-characters in each component and
- Up to 255-characters in a complete name



# The DNS Namespace (2)

---

## □ gTLDs

- generic Top-Level Domains, including:
- com: commercial organization, such as ibm.com
- edu: educational organization, such as purdue.edu
- gov: government organization, such as nasa.gov
- mil: military organization, such as navy.mil
- net: network infrastructure providing organization, such as hinet.net
- org: noncommercial organization, such as x11.org
- int: International organization, such as nato.int

ICANN – Internet Corporation for Assigned Names and Numbers  
<http://www.icann.org/>

# The DNS Namespace (3)

---

## □ New gTLDs launched in year 2000:

- aero: for air-transport industry
- biz: for business
- coop: for cooperatives
- info: for all uses
- museum: for museum
- name: for individuals
- pro: for professionals


# The DNS Namespace (4)

---

## □ Other than US, ccTLD

- country code TLD (ISO 3166)
  - Taiwan → tw
  - Japan → jp
- Follow or not follow US-like scheme
  - US-like scheme example
    - edu.tw, com.tw, gov.tw
  - Other scheme
    - co.jp, ac.jp

# DNS Namespace (5)




# How DNS Works

## – DNS Delegation

### □ Administration delegation

- Each domain can delegate responsibility to subdomain




# How DNS Works

## – DNS query process

### □ Recursive query process

- Ex: query lair.cs.colorado.edu → vangogh.cs.berkeley.edu,  
name server “ns.cs.colorado.edu” has no cache data





# DNS Delegation

## – Administrated Zone

### □ Zone

- Autonomously administered piece of namespace
  - Once the subdomain becomes a zone, it is independent to its parent
    - Even parent contains NS's A record



# DNS Delegation

## – Administrated Zone

### □ Zone

- Autonomously administered piece of namespace

### □ Two kinds of zone files

- Forward Zone files
  - Hostname-to-Address mapping
  - Ex:
    - bsd1 IN A 140.113.235.131
- Reverse Zone files
  - Address-to-Hostname mapping
  - Ex:
    - 131.235.113.140 IN PTR bsd1.cs.nctu.edu.tw.
- Forward zone is necessary

# The Name Server Taxonomy (1)

## □ Categories of name servers

- Based on a name server's source of data
  - **Authoritative**: official representative of a zone
    - **Master**: get zone data from disk
    - **Slave**: copy zone data from master
  - **Nonauthoritative**: answer a query from cache
    - **caching**: cashes data from previous queries
- Based on the type of data saved
  - **Stub**: a slave that copy only name server data (no host data)
- Based on the type of answers handed out
  - **Recursive**: do query for you until it return an answer or error
  - **Nonrecursive**: refer you to the authoritative server
- Based on the query path
  - **Forwarder**: performs queries on behalf of many clients with large cache

# The Name Server Taxonomy (2)

---

## □ Nonrecursive referral

- Hierarchical and longest known domain referral with cache data of other zone's name servers' addresses
- Ex:
  - Query lair.cs.colorado.edu from a nonrecursive server
  - Whether cache has
    - Name servers of cs.colorado.edu, colorado.edu, edu, root
- The resolver libraries do not understand referrals mostly. They expect the local name server to be recursive

# The Name Server Taxonomy (3)

---

## ❑ Caching


- Positive cache
- Negative cache
  - No host or domain matches the name queried
  - The type of data requested does not exist for this host
  - The server to ask is not responding
  - The server is unreachable of network problem

## ❑ Negative cache

- 60% DNS queries are failed
- To reduce the load of root servers, the authoritative negative answers must be cached

# The Name Server Taxonomy (4)


## □ Caching and forwarder DNS server



# The Name Server Taxonomy (5)

- How to arrange your DNS servers?

- Ex:



# The Name Server Taxonomy (6)

## □ Root name servers

- List in named.root file of BIND

.	3600000	IN	NS	A.ROOT-SERVERS.NET.
A.ROOT-SERVERS.NET.	3600000	A		198.41.0.4
.	3600000	NS		B.ROOT-SERVERS.NET.
B.ROOT-SERVERS.NET.	3600000	A		192.228.79.201
.	3600000	NS		C.ROOT-SERVERS.NET.
C.ROOT-SERVERS.NET.	3600000	A		192.33.4.12
.	3600000	NS		D.ROOT-SERVERS.NET.
D.ROOT-SERVERS.NET.	3600000	A		128.8.10.90
.	3600000	NS		E.ROOT-SERVERS.NET.
E.ROOT-SERVERS.NET.	3600000	A		192.203.230.10
.	3600000	NS		F.ROOT-SERVERS.NET.
F.ROOT-SERVERS.NET.	3600000	A		192.5.5.241
.	3600000	NS		G.ROOT-SERVERS.NET.
G.ROOT-SERVERS.NET.	3600000	A		192.112.36.4
.	3600000	NS		H.ROOT-SERVERS.NET.
H.ROOT-SERVERS.NET.	3600000	A		128.63.2.53
.	3600000	NS		I.ROOT-SERVERS.NET.
I.ROOT-SERVERS.NET.	3600000	A		192.36.148.17
.	3600000	NS		J.ROOT-SERVERS.NET.
J.ROOT-SERVERS.NET.	3600000	A		192.58.128.30
.	3600000	NS		K.ROOT-SERVERS.NET.
K.ROOT-SERVERS.NET.	3600000	A		193.0.14.129
.	3600000	NS		L.ROOT-SERVERS.NET.
L.ROOT-SERVERS.NET.	3600000	A		198.32.64.12
.	3600000	NS		M.ROOT-SERVERS.NET.
M.ROOT-SERVERS.NET.	3600000	A		202.12.27.33

# DNS Client

---

- ❑ /etc/resolv.conf

- nameserver, domain, search

- ❑ /etc/hosts